

MUNCKHOF

Piggy Back Sprayer

MUNCKHOF CONVENTIONAL OUTPUT SPRAYERS PROVIDE EXCELLENT CANOPY COVERAGE IN STAND ALONE ORCHARD TREES, AND UTILIZES A LARGE POWERFUL FAN TO DELIVER MATERIAL TO THE UPPER-MOST BRANCHES



AVAILABLE SIZES

200 L (50 US GAL.) FIBERGLASS
300 L (80 US GAL.) FIBERGLASS
400 L (100 US GAL.) FIBERGLASS
600 L (160 US GAL.) FIBERGLASS



- SLIM DESIGN
- DURABLE, TIME TESTED
- 3 POINT HITCH MOUNTED
- PTO DRIVEN

Munckhof Manufacturing

Box 308
Oliver British Columbia
V0H 1T0

Tel: 250.498.4426


Fax: 250.498.4460

Email: office@munckhof.com


www.munckhof.com



MUNCKHOF



A LARGE, CONVENIENT FILLER WITH NYLON STRAINER IS FITTED TO A DURABLE FIBREGLASS TANK. FIBREGLASS DOES NOT WORK HARDEN AND IS RELATIVELY EASY TO REPAIR.



A 3 WAY BALL VALVE SELECTS LEFT, RIGHT, OR BOTH BOOMS.

OPTIONAL ELECTRICAL VALVES AVAILABLE




MUNCKHOF SPRAYERS USE A POWERFUL 50LT/MIN 2-DIAPHRAGM PUMP WITH THROUGH PTO FOR FAN DRIVE.

MUNCKHOF ALSO FEATURES DOUBLE FILTRATION WITH SUCTION AND HIGH-PRESSURE FILTERS



MUNCKHOF CONVENTIONAL OUTPUT SYSTEMS FEATURE A GEARBOX WITH FAN SHUT-OFF FOR GUN SPRAYING

DOUBLE SWIVELING NOZZLE BODIES ALLOW FOR SELECTION OF TWO DIFFERENT SIZE NOZZLES OR USING THE "OFF" POSITION, ALUMINUM OXIDE NOZZLES COME STANDARD



A LARGE 610MM FAN PROVIDES A POWERFUL AIRSTREAM FOR SENDING MATERIAL THROUGH THE ENTIRE CANOPY, A BELT DRIVE IS USED TO REDUCE SHOCK LOADS ON THE DRIVE-TRAIN

