

# MUNCKHOF

## *Pull-Type Sprayer*

USE OF THE MUNCKHOF "HAZE TECHNIQUE" SPRAYING SYSTEMS HAS SHOWN A PROVEN SAVINGS OF UP TO 60% SPRAY MATERIALS WHEN USED IN VINEYARDS AND HIGH DENSITY ORCHARDS APPLICATIONS



### AVAILABLE CONFIGURATIONS

AIR BLAST (NON TOWER)  
GALVANIZED TOWER (PICTURED)

- SLIM DESIGN
- DURABLE & TIME TESTED
- 1000LT (250 US GAL.) CAPACITY
- PTO DRIVEN

### Munckhof Manufacturing

Box 308  
Oliver British Columbia  
V0H 1T0  
Tel: 250.498.4426  
Fax: 250.498.4460  
Email: [office@munckhof.com](mailto:office@munckhof.com)  
[www.munckhof.com](http://www.munckhof.com)



# MUNCKHOF



A LARGE, CONVENIENT FILLER WITH NYLON STRAINER IS FITTED TO A DURABLE FIBERGLASS TANK. FIBERGLASS DOES NOT WORK HARDEN AND IS REALITIVLY EASY TO REPAIR.



A 3 WAY BALL VALVE SELECTS LEFT, RIGHT, OR BOTH BOOMS.

OPTIONAL ELECTICAL VALVES AVAILABLE



MUNCKHOF 1000 LT SPRAYERS USE A POWERFULL 70 LT/MIN PLUNGER PUMP WITH THROUGH PTO FOR FAN DRIVE.

MUNCKHOF ALSO FEATURES DOUBLE FILTRATION WITH SUCTION AND HIGH PRESSURE FILTERS.



BY PLACING THE NOZZLES OUTSIDE THE AIR STREAM, AN EVEN SPRAY WITH CONSISTANT DROPLET SIZE IS BLOWN AT A 7 DEGREE ANGLE UPWARDS UNDER THE LEAVES AND INTO THE CANOPY. NOZZLES ARE ALUMINIUM OXIDE (ALMOST DIAMOND HARD) AND FITTED WITH SWIVELING NON-DRIP BODIES.



THE MUNCKHOF TOWERS ARE DESIGNED TO EVENLY DISTRIBUTE AIR FLOW THROUGH OUT THE ENTIRE HEIGHT OF THE CANOPY PLACING SPRAY MATERIAL ONLY WHERE IT IS NEEDED.

